

YOUR PERFECT SYSTEM



Wöhler VIS 260 Inspection Camera

Miniature Camera Head Ø 26 mm | 20 m push rod
Article no. 14261 J

Accessories



Wöhler L 200 Locator
Article no. 7430 J



Guidance Sleeve with protection cage
Article no. 3847 J

TECHNOLOGY AT A GLANCE

Wöhler Miniature Camera Head

Diameter:	Ø 26 x 38 mm
Resolution:	720 x 576 px (PAL) / 720 x 480 px (NTSC)
Image capture angle:	diagonal 145°
Light source:	White LEDs (12 bulbs)
Degree of protection:	Waterproof IP 68
Transmission frequency:	9.2 kHz

Monitor

TFT-Display:	7" / 16:9 Format
Resolution:	1,024 x 600 px
Power supply:	USB-C 5V / 3A
Battery:	3.7 V / 11.4 Ah
Battery operating time:	4 h
Dimensions:	245 x 141 x 53 mm (L x W x H)
Weight:	710 g

Camera Push Rod

Length:	20 m
Areas of application:	DN 40 – DN 70 pipes
Arcability:	Several 87° bends

Total Weight

Case:	8.6 kg
-------	--------



SCAN NOW &
LEARN MORE

WÖHLER

Wöhler Technik GmbH
Headquarters Germany
Wöhler-Platz 1 · 33181 Bad Wünnenberg
www.woehler-international.com

Call us or mail us to get more information!

We would be happy to explain to you what the Wöhler VIS 260 Inspection Camera can do!

+49 2953 73 100 or international@woehler.de

WÖHLER

NEW

YOUR PROBLEM SOLVER
FOR EVERYDAY LIFE
FAST DAMAGE LOCATION
IN SMALL PIPES



The new Wöhler
VIS 260 Inspection Camera

Made in Germany



SLIM IN THE PIPE EASY TO HANDLE

With the new Wöhler VIS 260 Inspection Camera, inspecting small pipes is a breeze. The robust case system and slim 26 mm mini camera head can handle even multiple 90° bends and ensure quick start-up and reliable results – ideal for anyone who values clear solutions in everyday life.



LOCATE WITH PRECISION

The integrated transmitter in the camera head allows you to determine the exact position at a glance ideal for effective damage repair and perfect connection to the optional Wöhler L 200 Locator.

THE SPECIALIST FOR SMALL PIPES

The 26 mm mini head is designed for pipes measuring 40–70 mm. The handy 20-metre camera rod is ideal for typical HVAC pipes such as household drains and kitchen drains. Even multiple 90° bends in sewage, drain and underground pipes are no problem for the bendable camera rod.

NOTICEABLY FAST, VISIBLY SIMPLE

With the tried-and-tested all-in-one case system, you have everything right at your fingertips. No setting up, no searching: Open the case, switch the camera on, and get started. Easy to transport, quick to set up – from room to room or directly on the construction site, ready for use anywhere.

CLEANING THE WAY IT SHOULD BE

After the inspection, simply remove the camera rod from the separate compartment and clean it in no time at all – hygienic and ready for the next use.

EXTREMELY SHARP & PRECISE

The bright TFT colour monitor provides you with razor-sharp, colour-accurate images while displaying the exact distance in the pipe – for clear findings, confident decisions and reliable orientation during the inspection.

DOCUMENTATION MADE EASY

You can save photos and videos directly to the internal memory or a USB stick. This allows you to record your results for customers and as evidence.

